



# Line Lifters

## Energized Line Lifter

- Capacity: 1,000/2,500/4,000 lbs
- Clear span fiberglass: 5'6"/10'/15'
- Support an energized conductor from a crane



## Folding Guard Arm

- 1,000 lb Capacity
- Weight: 450 lbs
- Mounts to boom trucks and digger derricks
- 3 Lifting rings assist in mounting



XHD Option

## Horizontal/Vertical Auxiliary Arm

- Balanced vertical load: 1,350 lbs
- 5' mast has 4' clear span fiberglass
- 12' arm has 5' clear span fiberglass
- Fits on crane, bucket truck and derrick boom tip

## Bundle Lifter

- 3,500 lb capacity
- 10-12 ft clear span fiberglass
- Picks up yoke plate & keeps it vertical



## Roller Lifter

### Single/Dual/Heavy Duty

- High Strength Steel
- Weight: 15-65 lbs
- Working Load: 2,000-10,000 lbs

# Next Generation Insulated Work Platforms

## Hydraulic IWP

- 765 kV Bare Hand Work
- 15 years in the field
- Working Height up to 209'
- Hydraulically articulated
- 1,200 lb Yoke Basket
- 900-1,200 lb Rotating Basket
- Bundle Lifter Option
- HPU at boom tip
- TRIED AND PROVEN

*Overhead and Substation Applications*



INSPIRED BY LINEMEN TESTED BY LINEMEN TRUSTED BY LINEMEN

# Pole Pullers

## XHD-60 & HD-30 Pole Puller

- Strong and efficient
- Capacity - 120,000 and 60,000 lbs
- Unique Jaws to Grab Pole
- Stub Puller Attachment



# Job Specific Tools

## Tool Carrier

- 3 Tool Options: Horizontal Tool (adjusts from 12"-18"), 12" and 18" Vertical Tool.
- High strength & light weight
- Can be easily attached from the 12' fiberglass pole
- 3,500-10,500 lb capacity



## Unigain

- Symmetrical Loading Capacity (per conductor)
  - 3,750 lb (Dead-End)
  - 1,000 lb (Tangent)
- 12 ft fiberglass crossarm with up to 7 ft offset
- Innovative solution for re-conductoring and emergency repairs
- Overall cost reduction on repairs
- Rated to hold energized conductors



U.S. Patent No. 7,578,488

## Hot Line Base Plate

- 1,600/8,000 lb Capacity
- Innovative solution to temporarily hold a conductor in place during emergency repairs

U.S. Patent No. 8,299,357 & 7,750,236



# Triple Line Lifters



## TLL-1300/2500

- 1,300/2500 lb vertical load per conductor
- Hydraulic articulation, extension & retraction
- Quick attach insulators & wire holders
- Works with vertical & horizontal construction
- Handheld radio remote control
- Mounts to cranes & boom trucks
- Conductor spacing: 6.5' - 14.5'
- Installed at ground level



## TLL-2000

- 2,000 lb vertical load per conductor
- 200 lb side load per conductor
- Polymer or fiberglass insulators
- Works with vertical & horizontal construction
- Conductor spacing: 6.5' - 14.5'
- Stows on side of crane
- Mounts to cranes, boom trucks & digger derricks
- HPU at boom tip



Patent Pending

## Buddy Bushing

- Safety
- Reliability
- Process Improvement
- Simplification
- Risk Mitigation
- Inner Bushing Rotates
- HUGE Cost Reduction on Repairs



U.S. Patent No. 8,399,770



**\*\*\*PROBLEM\*\*\***

**Erosion of the attachment hole in the arm due to vibrations**

**\*\*SOLUTION\*\***

**Buddy Bushing inserted into attachment hole in cross arm**

# LineWise

By Diversified Products

1001 Webster Ave.  
Waco, TX 76706

254-757-1177

www.line-wise.com

noahg@diversifiedproduct.com

©2017 Diversified Products

*Photos and diagrams are for promotional purposes only.*

*Product design and specifications may change without notice or obligation.*

# LineWise

Utility Products by  
Diversified Products

