

LINEWISE[®]

Pole Puller



254-757-1177 | sales@line-wise.com | line-wise.com

SPECIFICATIONS

	PP-30-HD	PP-60-XHD
Performance	Pull (lb.) at 2,500 psi 60,000	Pull (lb.) at 2,250 psi 125,000
Max. Pole Size	18" Diameter 56" Circumference	26" Diameter 81" Circumference
Cylinder	Stroke 24" Bore 4" Rod 3"	Stroke 24" Bore 6" Rod 4"
Head	Beveled teeth on cam action head provide better grip. Chain (2) 1/2" Grade 100	Beveled teeth on cam action head provide better grip. Chain (2) 3/4" Grade 100
Base Weldment	Exterior 32" x 32" Interior 20" x 26" Weight 700 lbs.	Exterior 46" x 46" Interior 28" x 28" Weight 1,500 lbs.
Lifting Points	2 lifting eyes on the head Fork pockets: 2.5" x 5.5" x 32" long	2 lifting eyes on the head Fork pockets: 3.25" x 7.25" x 46" long
Controls	Utilize controls on a power source (skid steer, crane or derrick)	Utilize controls on a power source (skid steer, crane or derrick)
Hydraulics	Required flow rate 5-15 gpm @ 2,500 psi Storage of hoses on base (2) 25 ft long	Required flow rate 5-15 gpm @ 2,500 psi Storage of hoses on base (2) 25 ft long

STUB PULLER OPTION



Stub Puller option allows removal of poles that have been cut off above ground level, but at a height too low to pull out with the standard Pole Puller.

Pole Puller successfully removes poles that are foamed in rocky soil!



INSPIRED BY LINEMEN TESTED BY LINEMEN TRUSTED BY LINEMEN

Material and specifications are subject to change without notice. Units in photos may include optional features. Contact a LineWise representative for available options. LineWise® and the LineWise logo are registered trademarks of Fritel & Associates, LLC and may not be used without permission.
© 2021 Diversified Product Development All Rights Reserved.