| | · | · |
|---------------------|--------------------|-----------------|
| | SGWH 2500 | SGWH 500 |
| Capacity | | |
| Downward Load | 2500 lb (1134 kg) | 500 lb (227 kg) |
| Side Load | 2500 lb (1134 kg) | 500 lb (227 kg) |
| Gate Load | 500 lb (227 kg) | 200 lb (91 kg) |
| Vert. Construction | Yes | Yes |
| Horiz. Construction | Yes | Yes |
| Wire Diameter Size | 2" and below | 2" and below |
| Weight | 45 lb (20 kg) | 11 lb (5 kg) |
| Product Uses | TLL-1300/2000/2500 | TLL-500A-S1 |
| | HLL-10-4000/8000 | TLL-500A-S3 |



FEATURES

- SGWH 500 is a direct replacement for the current wire holder on the market
- Can be adapted to fit the material handling jib on most bucket trucks
- The only wire holder on the market with a load-rated gate; used in horizontal & vertical construction
- (2) side swinging redundant gates that can be opened individually or together by hand or hotstick
- 360° aluminum rollers around conductor to protect and keep everything at the same potential















INSPIRED BY LINEMEN TESTED BY LINEMEN TRUSTED BY LINEMEN



Material and specifications are subject to change without notice. Units in photos may include optional features. Contact a LineWise representative for available options. LineWise* and the LineWise logo are registered trademarks of Fritel & Associates, LLC and may not be used without permission. © 2022 Diversified Product Development All Rights Reserved. Patent Pending

