

TLL-300B



Voltage (#) Phases	Capacity per Phase	Mast
up to 34.5kV (3)	300 lb	31"
Crossarm	Construction	
8'	Horizontal	
Components	Mounting	
Mostly Fiberglass	Bucket Truck	

TLL-450



Voltage (#) Phases	Capacity per Phase	Mast
up to 72.5kV (3)	450 lb	4'
Crossarm	Construction	
12'	Horizontal	
Components	Mounting	
Mostly Fiberglass	Digger Derrick/Crane	

TLL-500A Series 1 & 2



Voltage (#) Phases	Capacity per Phase	Construction
up to 72.5kV (3)	500 lb (Terex) 300 lb (Altec)	Horizontal & Vertical
Max Phase Spacing	Components	Mounting
Outside to Outside - 16' Center to Outside - 8'	Steel, Aluminum, Polymer Insulators	Digger Derrick/ Crane



TLL-300D



Voltage (#) Phases	Capacity per Phase	Mast
up to 34.5kV (3) with 3' mast	300 lb	12" or 31"
Crossarm	Construction	
10'	Horizontal & Vertical	
Components	Mounting	
Mostly Fiberglass	Digger Derrick/Crane	

TLL-500



Voltage (#) Phases	Capacity per Phase	Mast
up to 72.5kV (3) with 3' mast	500 lb (Terex) 500 lb tangent loading 300 lb (Altec)	1' or 3'
Crossarm	Construction	
9' or 12'	Horizontal & Vertical	
Components	Mounting	
Mostly Fiberglass	Digger Derrick/Crane	

TLL-500A Series 3



Voltage (#) Phases	Capacity per Phase	Construction
up to 72.5kV (3)	500 lb (Terex) 300 lb (Altec)	Horizontal & Vertical
Max Phase Spacing	Min Phase Spacing	
Outside to Outside - 16' Center to Outside - 8'	Center to Outside - 3' 11"	
Hydraulic	Components	Mounting
Yes - Articulation, Extension & Retraction	Steel, Aluminum, Polymer Insulators	Digger Derrick/ Crane

TLL-1300



Voltage (#) Phases	Capacity per Phase	Construction
69kV (3) 115kV (3) 138kV (3) 161kV (3) 230kV (2)	1300 lb 1300 lb 1200 lb 1100 lb consult factory	Horizontal & Vertical
Max Phase Spacing		Min Phase Spacing
Outside to Outside - 29' Center to Outside - 14' 6"		Center to Outside - 6' 6"
Hydraulic	Components	Mounting
Yes - Articulation, Extension & Retraction	Steel, Fiberglass Insulators	Crane

TLL-2500



Voltage (#) Phases	Capacity per Phase	Construction
115kV (3) 138kV (3) 161kV (3) 230kV (3) 345kV (2)	2500 lb	Horizontal & Vertical
Max Phase Spacing		Min Phase Spacing
Outside to Outside - 48' Center to Outside - 24'		Center to Outside - 10'
Hydraulic	Components	Mounting
Yes - Articulation, Extension & Retraction	Steel, Fiberglass Insulators	Crane

TLL-2000 Series 3



Voltage (#) Phases	Capacity per Phase	Construction
115kV (3) 138kV (3) 161kV (3) 230kV (2)	2000 lb	Horizontal & Vertical
Max Phase Spacing		Min Phase Spacing
Outside to Outside - 48' Center to Outside - 24'		Center to Outside - 12'
Hydraulic	Components	Mounting
Yes - Articulation, Extension & Retraction	Steel, Fiberglass Insulators	Crane



700 Research Ave.
Waco, TX 76705

254-757-1177
line-wise.com
sales@line-wise.com



INSPIRED BY LINEMEN TESTED BY LINEMEN TRUSTED BY LINEMEN

LineWise® and the LineWise logo are registered trademarks of Fritel & Associates, LLC and may not be used without permission.

© 2022 Diversified Product Development All Rights Reserved.



Triple Line Lifters

