

**LINEWISE**<sup>®</sup>

**Pole Puller**




254-757-1177 | [sales@line-wise.com](mailto:sales@line-wise.com) | [line-wise.com](http://line-wise.com)



# SPECIFICATIONS

	<b>PP-60-XHD</b>
Performance	Pull (lb.) at 2,250 psi 125,000
Max. Pole Size	26" Diameter 81" Circumference
Cylinder	Stroke 24" Bore 6" Rod 4"
Head	Beveled teeth on cam action head provide better grip. Chain (2) 3/4" Grade 100
Base Weldment	Exterior 46" x 46" Interior 28" x 28" Weight 1,500 lbs.
Lifting Points	2 lifting eyes on the head Fork pockets: 3.25" x 7.25" x 46" long
Controls	Utilize controls on a power source (skid steer, crane or derrick)
Hydraulics	Required flow rate 5-15 gpm @ 2,500 psi Storage of hoses on base (2) 25 ft long

## STUB PULLER OPTION



Stub Puller option allows removal of poles that have been cut off above ground level, but at a height too low to pull out with the standard Pole Puller.

*Pole Puller successfully removes poles that are foamed in rocky soil!*



INSPIRED BY LINEMEN TESTED BY LINEMEN TRUSTED BY LINEMEN

Material and specifications are subject to change without notice. Units in photos may include optional features. Contact a LineWise representative for available options. LineWise® and the LineWise logo are registered trademarks of Fritel & Associates, LLC and may not be used without permission.  
© 2023 Diversified Product Development All Rights Reserved.