

LINEWISE

Hot Jib



Upgrade your material handling jib with a SGWH500. The only load rated gate in the electric utility industry!

254-757-1177 | sales@line-wise.com | line-wise.com

SPECIFICATIONS

Capacity	Same as OEM
Vertical Load Capacity	Same as OEM
Weight	36 - 60 lbs
Clear Span Insulation	28" - 36"

OPTIONS



Cut away view shows interior construction including moisture removing desiccant canister and bonded in place pin bosses

	SGWH 500
Capacity	
Downward Load	500 lb (227 kg)
Side Load	500 lb (227 kg)
Gate Load	200 lb (91 kg)
Vert. Construction	Yes
Horiz. Construction	Yes
Wire Diameter Size	2" and below
Weight	11 lb (5 kg)

FEATURES

- Meet or exceed ASTM F711, OSHA 1926.957, WAC 296-45-305
- Certified for holding energized powerlines
- Available in 3 sizes: round, rectangular and square
- Sealed with LineWise desiccant canister system which traps moisture and prevents contaminants from entering the jib, keeping the inside clean and dry.
- Dessicant is easily re-freshened
- Interchangeable with existing hydraulic/manual extendable jibs
- Steel components are plated for rust protection



SGWH500 fits with a standard 3in diameter extension of your material handling jib.

LineWise



INSPIRED BY LINEMEN TESTED BY LINEMEN TRUSTED BY LINEMEN

Material and specifications are subject to change without notice. Units in photos may include optional features. Contact a LineWise representative for available options. LineWise® and the LineWise logo are registered trademarks of Fritel & Associates, LLC and may not be used without permission.
© 2024 Diversified Product Development All Rights Reserved.



254-757-1177 | sales@line-wise.com | line-wise.com