

SPECIFICATIONS

SPECIFI	CATIONS
Dimensions	60" x 91.5" x 81" tall 1422 mm x 2311 mm x 2057 mm tall
Capacity	600 lb (272 kg)
Weight	950 lb (430 kg)
Max Speed	4 mph
Conductor Diameter	1" - 2" (25 mm - 51 mm) max 2.5" with armor rod (64 mm)
Performance	2x 1.9kW main drive motors direct mounted to wheel2x1.9kW secondary drive motors direct mounted to wheelAll day power provided by 2x 48V 30Ah batteries
Wheels	6 upper wheels; 4x rubber drive wheels electrically driven and 2x composite idlers Each main wheel support rotates laterally for passing yoke plates, insulators & spacers Center main wheels raise/lower so each set of main rollers can be removed from conductors Vertically actuated lower roller for third conductor 7.5" outer diameter, 5.8" inside diameter rubber coated drive wheel
Braking	Dynamic provided by electric drive system
Construction	Aluminum Alloy; Welded & Bolted
Occupancy	1 Person

FEATURES

- 20° climb angle; wheels specifically engineered for no slip
- Configured for 3 conductors (18" between conductor)
- 30.5" between roller assemblies
- Cradle to place Tri-bundle Line Cart on to the conductors using crane or helicopter
- Retractable hooks for spacer storage
- Customized tool storage

- Folding seat
- Parking brake included
- Safety tube secured across wheels in case conductor comes off
- Floor openings less than 0.5"
- 2 or 3 bundles
- Electric linear actuators for wheel articulation

Contact LineWise to discuss your line

cart needs!

- Battery or gas/hydraulic powered
- Can be configured for bonded work



Material and specifications are subject to change without notice. Units in photos may include optional features. Contact a LineWise representative for available options. LineWise® and the LineWise logo are registered trademarks of Fritel & Associates, LLC and may not be used without permission. © 2025 Diversified Product Development All Rights Reserved.

254-757-1177 | sales@line-wise.com | line-wise.com