

LINEWISE

Hot Jib



*Upgrade your material
handling jib with a SGWH500.
The only load rated gate in the
electric utility industry!*

SPECIFICATIONS

| | |
|------------------------|-----------------------------|
| Capacity | Same as OEM |
| Vertical Load Capacity | Same as OEM |
| Weight | 36 - 60 lbs |
| Clear Span Insulation | 28" - 36" (711 - 914 mm) |

OPTIONS



FEATURES

- Meet or exceed ASTM F711, OSHA 1926.957, WAC 296-45-305
- Certified for holding energized powerlines
- Available in 3 sizes: round, rectangular and square
- Sealed with LineWise desiccant canister system which traps moisture and prevents contaminants from entering the jib, keeping the inside clean and dry.
- Dessicant is easily re-freshened
- Interchangeable with existing hydraulic/manual extendable jibs
- Steel components are plated for rust protection



Cut away view shows interior construction including moisture removing desiccant canister and bonded in place pin bosses

| | SGWH - 750 |
|---------------------|----------------------|
| Capacity | |
| Downward Load | 750 lb (340 kg) |
| Side Load | 750 lb (340 kg) |
| Gate Load | 200 lb (91 kg) |
| Vert. Construction | Yes |
| Horiz. Construction | Yes |
| Wire Diameter Size | 2" (51 mm) and below |
| Weight | 11 lb (5 kg) |



SGWH - 750 fits with a standard 3" (76 mm) diameter extension of your material handling jib.

INSPIRED,TM
TESTED,
AND TRUSTED
BY LINEWORKERS



LineWise

Material and specifications are subject to change without notice. Units in photos may include optional features. Contact a LineWise representative for available options. LineWise® and the LineWise logo are registered trademarks of Fritel & Associates, LLC and may not be used without permission.
© 2025 Diversified Product Development All Rights Reserved.



254-757-1177 | sales@line-wise.com | line-wise.com