

SPECIFICATIONS

	·
Dimensions	26" x 48" x 60" tall
	660 mm x 1219 mm x 1524 mm tall
Capacity	550 lb (250 kg)
Weight	175 lb (80 kg)
Conductor	1" - 3" (25 mm - 76 mm) including armor rod
Diameter	
Performance	4 x 200 watt drive motors direct mounted to wheel
	All day power provided by 2 x 24 Volt 47 mAh battery
Wheels	2x aluminum and 2x rubber drive wheels electrically driven
Max Speed	5 mph (6.4 km/h)
Braking	Dynamic provided by electric drive system and mechanical park brake
Construction	Titanium Alloy; Welded & Bolted
Occupancy	1 Person

FEATURES

• 19° climb angle; wheels specifically engineered for no slip

- For use with:
 - Tri-bundle conductor 16" x 16" x 16" (406 mm x 406 mm x 406 mm)
 - Horizontal double conductor 16" 25" (406 mm 635 mm)
- Safety lifting sling to place Cart on the conductors using crane or helicopter
- Collapsible Safety Net
- Parking brake included
- Dynamic Braking
- 2 or 3 bundles
- Electric Powered















Contact LineWise to discuss your line

cart needs!

Material and specifications are subject to change without notice. Units in photos may include optional features. Contact a LineWise representative for available options. LineWise® and the LineWise logo are registered trademarks of Fritel & Associates, LLC and may not be used without permission.

© 2025 Diversified Product Development All Rights Reserved.

