


SPECIFICA	ATTONS	
Dimensions	60" x 91.5" x 81" tall 1524 x 2324 x 2057 (mm) tall	- CA
Operation	Electric-powered	
# of Conductors	Tri-bundle Tri-bundle	
Capacity	600 lb (272 kg)	
Weight	950 lb (431 kg)	
Max Speed	4 mph	
Conductor Diameter	1" - 2.5" (25 mm - 64 mm) including armor rod	
Performance	Qty (2) 1.9kW main drive motors direct mounted to wheel Qty (2) 1.9kW secondary drive motors direct mounted to wheel All day power provided by qty (2) 48 volt 30Ah batteries	
	6 upper wheels; qty (4) rubber drive wheels electrically driven and qty (2) composite idl Each main wheel support rotates laterally for passing yoke plates, insulators & spacers	ers

Vertically actuated lower roller for third conductor

Dynamic provided by electric drive system

Aluminum Alloy; Welded & Bolted



Contact LineWise to discuss your line cart needs!

## **FEATURES**

Wheels

Braking

Construction

Occupancy

- 20° climb angle; wheels specifically engineered for no slip
- Configured for 3 conductors; 18" (457 mm) between conductor

1 Person

- 30.5" (775 mm) between roller assemblies
- Cradle to place Pioneer 3E Line Cart on to the conductors using crane or helicopter
- Retractable hooks for spacer storage
- Customized tool storage

- Folding seat
- Parking brake included

Center main wheels raise/lower so each set of main rollers can be removed from conductors

7.5" (191 mm) outer diameter, 5.8" (147 mm) inside diameter rubber coated drive wheel

• Safety tubes are secured across the wheels to support the cart in case a wheel slips off a conductor

- Floor openings less than 0.5" (13 mm)
- 2 or 3 bundles
- Electric linear actuators for wheel articulation
- Electric or gas/hydraulic powered
- Can be configured for bonded work















Material and specifications are subject to change without notice. Units in photos may include optional features. Contact a LineWise representative for available options. LineWise\* and the LineWise logo are registered trademarks of Fritel & Associates, LLC and may not be used without permission. © 2025 Diversified Product Development All Rights Reserved.

