

LINEWISE®



Anchor Tester

254-757-1177 | sales@line-wise.com | line-wise.com

SPECIFICATIONS

Max Operating Pressure	2,200 psi (15,168 kPa)
Max Total Pull Force Capacity	45,000 lb (20,412 kg)
Pressure for Retract	
45,000 lb (20,412 kg)	2200 psi (15,168 kPa)
40,000 lb (18,144 kg)	1950 psi (13,445 kPa)
30,000 lb (13,608 kg)	1450 psi (9997 kPa)
20,000 lb (9072 kg)	1000 psi (6895 kPa)
10,000 lb (4536 kg)	500 psi (3447 kPa)
Max Cylinder Stroke	16" (406 mm)
Weight	1500 lb (680 kg)
Width	42" (1067 mm)
Depth	86.3" (2192 mm)
Height of Threaded Adjustment Rod	
Collapsed (Retracted)	66.4" (1687 mm)
Max Height (Extended)	78.8" (2002 mm)
Angle Adjustment	50°-100°



FEATURES

- Provides a pin with +/- 1.5" (38 mm) of side shift, a threaded rod with 12" (305 mm) of adjustment vertically, and a 16" (406 mm) stroke cylinder that can rotate 360° about its axis with spherical bearings that allow for 5° of tilt from its axis
- Allows testing of square shaft multi-helix screw anchors
- Features skid steer style quick attach, tie down points, and lift points
- Digital readout load cell (potential add-on)

INSPIRED,[™]
TESTED,
AND TRUSTED
BY LINEWORKERS



LineWise

Material and specifications are subject to change without notice. Units in photos may include optional features. Contact a LineWise representative for available options. LineWise® and the LineWise logo are registered trademarks of Diversified Product Development and may not be used without permission. © 2025 Diversified Product Development All Rights Reserved.



254-757-1177 | sales@line-wise.com | line-wise.com