

## **SPECIFICATIONS**

Dimensions	32" x 64" x 60" tall 813 x 1626 x 1524 (mm) tall
Operation	Electric-powered
# of Conductors	Double or Tri-bundle
Capacity	550 lb (250 kg)
Weight	175 lb (80 kg)
Conductor Diameter	1" - 3" (25 mm - 76 mm) including armor rod
Performance	Qty (4) 200 watt drive motors direct mounted to wheel All day power provided by qty (1) 24 volt 47 Ah battery
Wheels	Qty (2) aluminum and qty (2) rubber drive wheels electrically driven
Max Speed	5 mph (6.4 km/h)
Braking	Dynamic provided by electric drive system and mechanical park brake
Construction	Titanium Alloy and Aluminum; Welded & Bolted
Occupancy	1 Person

## **FEATURES**

- 19° climb angle; wheels specifically engineered for no slip
- For use with:
  - Tri-bundle 16" 25" (406 mm 635 mm)
  - Horizontal double-bundle 16" 25" (406 mm 635 mm)
- Lifting sling to place Cart on the conductors using lifting device
- Parking brake included
- Dynamic braking and park brake
- Electric-powered

## **OPTIONS**

- Tower jumper kit
  - T-Bar
  - Rope jumper

- Spanometer measure distance traveled
- Grounding wheel
- Collapsible safety net















Contact LineWise

to discuss your line

cart needs!

Material and specifications are subject to change without notice. Units in photos may include optional features. Contact a LineWise representative for available options. LineWise® and the LineWise logo are registered trademarks of Fritel & Associates, LLC and may not be used without permission.

© 2025 Diversified Product Development All Rights Reserved.

