TLL-300B

Voltage (#) Phases	Capacity per Position	Mast
up to 34.5 kV (3)	300 lb (8' crossarm) 240 lb (10' crossarm)	26.5" or 32.5"
Crossarm	*Construction*	
8' or 10'	Horizontal	
Components	*Mounting*	
Mostly Fiberglass	Bucket Truck	

TLL-300D

Voltage (#) Phases	Capacity per Position	Mast
up to 34.5 kV (3)	300 lb	31"
Crossarm	*Construction*	
8' or 10'	Horizontal & Vertical	
Components	*Mounting*	
Mostly Fiberglass	Digger Derrick/Crane	

TLL-500

Voltage (#) Phases	Capacity per Position	Mast
up to 72.5 kV (3) with 3' mast	500 lb (Terex) 500 lb tangent loading 300 lb (Altec)	1' or 3'
Crossarm	*Construction*	
9' or 12'	Horizontal & Vertical	
Components	*Mounting*	
Mostly Fiberglass	Digger Derrick/Crane	

LineWise

TLL-500A Series 1

Voltage (#) Phases	Capacity per Position	Construction
up to 72.5 kV (3)	500 lb (Terex) 300 lb (Altec)	Horizontal & Vertical
Max Phase Spacing	*Components*	*Mounting*
Outside to Outside - 16' Center to Outside - 8'	Steel, Aluminum, Polymer Insulators	Digger Derrick/ Crane

TLL-500A Series 3

Voltage (#) Phases	Capacity per Position	Construction
up to 72.5 kV (3)	500 lb (Terex) 300 lb (Altec)	Horizontal & Vertical
Max Phase Spacing	*Min Phase Spacing*	
Outside to Outside - 16' Center to Outside - 8'	Center to Outside - 3' 11"	
Hydraulic	*Components*	*Mounting*
Yes - Articulation, Extension & Retraction	Steel, Aluminum, Polymer Insulators	Digger Derrick/ Crane

TLL-1300

Voltage (#) Phases	Capacity per Phase	Construction
69 kV (3) 115 kV (3) 138 kV (3) 161 kV (3) 230 kV (2)	1300 lb 1300 lb 1200 lb 1100 lb consult factory	Horizontal & Vertical
Max Phase Spacing	*Min Phase Spacing*	
Outside to Outside - 29' Center to Outside - 14' 6"	Center to Outside - 6' 6"	
Hydraulic	*Components*	*Mounting*
Yes - Articulation, Extension & Retraction	Steel, Fiberglass Insulators	Crane

TLL-2000 Series 3

Voltage (#) Phases	Capacity per Position	Construction
115 kV (3) 138 kV (3) 161 kV (3) 230 kV (3)	2000 lb	Horizontal & Vertical

Max Phase Spacing	Min Phase Spacing
Outside to Outside - 48’ Center to Outside - 24’	Center to Outside - 12’

Hydraulic	Components	Mounting
Yes - Articulation, Extension & Retraction	Steel, Fiberglass Insulators	Min. 50 Ton Crane

TLL-2500

Voltage (#) Phases	Capacity per Position	Construction
115 kV (3) 138 kV (3) 161 kV (3) 230 kV (3) 345 kV (2)	2500 lb	Horizontal & Vertical

Max Phase Spacing	Min Phase Spacing
Outside to Outside - 48’ Center to Outside - 24’	Center to Outside - 10’

Hydraulic	Components	Mounting
Yes - Articulation, Extension & Retraction	Steel, Fiberglass Insulators	Min. 80 Ton Crane

TLL-4000

Voltage (#) Phases	Capacity per Position	Construction
345 kV (3)	4000 lb	Horizontal & Vertical

Max Phase Spacing	Min Phase Spacing
Outside to Outside - 62’ Center to Outside - 31’	Center to Outside - 16’

Hydraulic	Components	Mounting
Yes - Articulation, Extension & Retraction	Steel, Fiberglass Insulators	Min. 200 Ton Crane

TLL-6000

consult factory

700 Research Ave. Waco, TX 76705

254-757-1177 | line-wise.com
sales@line-wise.com

INSPIRED,®
TESTED,
AND TRUSTED
BY LINEWORKERS

LineWise® and the LineWise logo are registered trademarks of Fritel & Associates, LLC and may not be used without permission.

© 2026 Diversified Product Development All Rights Reserved.

LineWise®

Triple Line Lifters